

FasTrack 29/29

FasTrack 2929 Woven Geotextile, 4100N, 173g/m² - 5.25m x 100m roll



UK
CA CE

DESCRIPTION

FasTrack 2929 Woven Geotextile, 4100N, 173g/m² - 5.25m x 100m roll

SPECIFICATION

General information

Stock code	GTSG/FASTRACK/2929
Range	FasTrack
Third party certified	UKCA CE
Roll sizes	5.25m x 100m
Geotextile product range	FasTrack

Geotextile properties

Material	Polypropylene
Tensile strength (MD)	EN ISO 10319 29kN/m
Tensile strength (CMD)	EN ISO 10319 29kN/m
Elongation at max load (MD)	EN ISO 10319 26%
Elongation at max load (CMD)	EN ISO 10319 26%
Static puncture resistance	EN ISO 12236 4.1kN
Dynamic perforation resistance	EN ISO 13433 11mm

CBR puncture resistance	EN ISO 12236	4100N
Dynamic cone drop	EN ISO 13433	11mm
Water permeability	EN ISO 11058	23L/m ² .s
Characteristic opening size	EN ISO 12956	330µm
Thickness under 2kPa	EN ISO 9863-1	1mm
Weight	EN ISO 9864	173g/m ²

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

