

ProtectaWeb 200-356

3.68m roll length, 200mm depth, suitable for site access for construction vehicles, cranes and working platforms



DESCRIPTION

3.68m roll length, 200mm depth, suitable for site access for construction vehicles, cranes and working platforms

SPECIFICATION

General information

Stock code	Protectaweb/200/356
Range	ProtectaWeb

Geocell

Material	High density polyethylene
Colour	Black
Density (g/cm3)	≥0.94
Carbon black content (%)	≥1.5
Tensile strength (MD)	20 kN/m
Tensile strength of perforated strip MD (kN/m)	10 kN/m
Elongation at max load	15%
Seam Peel Strength3 (N/100mm depth cell)	≥1420
Sheet length	3.68 m

Bonded ranges (mm)	356±2.5
Cell depth	200 mm
Expanded cell width	260 mm
Expanded cell length	224 mm
Number of cells per section	330
Expanded section width	2.71 m
Expanded section length	7.38 m
Expanded section area	20 m ²

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)

